

1060nm~1064nm 2W Multi-mode Fiber Coupled Laser System | Laser Source | APC Function Optional  
1064nm| MMF| Pigtail Turnkey Laser Source|2W Output Power| High Stability| TTL and Analog Modulation

## 1064nm 2W Multi-mode Fiber Coupled Laser Source

### Features:

- 1064nm
- With 105um Fiber
- Built-in TEC Cooling
- Output Power Adjustable
- TTL / Analog Modulation Optional
- APC Function Optional
- High Stability
- Long Lifetime



WAVESPECTRUM offer the **Turn-key Fiber Coupled Laser System**, the Wavelength is form 375nm to 1550nm, the Fiber Type can be **SM Fiber**, **PM Fiber** and **MM Fiber**. The Output Power is from 1mW to 50W. The Typical Wavelength is below:

375nm,405nm,445nm,488nm,520nm,532nm,635nm,650nm,660nm,670nm,685nm,785nm,808nm,830nm, 850nm,880nm,905nm,915nm,940nm,980nm,1064nm,1310nm,1450nm, 1470nm and 1550nm etc.

Our **Laser System** includes the **Fiber Coupled Laser Module**, **Power Supply** and **TEC Cooling System**. It is easy to use and with **High Reliability**, **High Stability**, **Long Lifetime**. The Laser System have passed the **ROHS** and **CE** Certification,

WAVESPECTRUM also offer the Customized Laser System, such as **Dual-Wavelength Laser System**, **Tri-Wavelength Laser System** and **Fiber Detachable Laser System**.

More information Please visit our website: [en.wavespectrum-laser.com.cn](http://en.wavespectrum-laser.com.cn)



Wavespectrum Laser, Inc.  
[www.wavespectrum-laser.com](http://www.wavespectrum-laser.com)  
[wavespectrumlaser@gmail.com](mailto:wavespectrumlaser@gmail.com)



| Specification            |                      | WSLS-1064-002-H                      |        |       |
|--------------------------|----------------------|--------------------------------------|--------|-------|
|                          |                      | Min                                  | Type   | Max   |
| Optical data             | Wavelength           | ±3nm                                 | 1064nm | ±15nm |
|                          | Output Power         | 0~2W adjustable                      |        |       |
|                          | Spectral Width       |                                      | 3nm    |       |
| Fiber data               | Fiber core           | 105um                                |        |       |
|                          | Fiber detachable     | Optional                             |        |       |
|                          | Fiber type           | Multi-mode                           |        |       |
|                          | Fiber Length         | >80cm                                |        |       |
|                          | Connector            | FC/SMA905                            |        |       |
| Control data             | Operation mode       | CW                                   |        |       |
|                          |                      | TTL Modulation (optional)            |        |       |
|                          |                      | Analog Modulation (optional)         |        |       |
|                          | Power stability      | 1%                                   | ----   | 3%    |
|                          | Noise (10Hz~100MHz)  | 0.5% rms                             | 1% rms |       |
|                          | APC Function         | Auto Power Control Function optional |        |       |
|                          | Cooling Way          | Built-in TEC cooling                 |        |       |
| Environmental Conditions | Operation Temp       | 0~40℃                                |        |       |
|                          | Storage Temp         | -20~55℃                              |        |       |
| Power supply             | AC (Standard)        | 90V~240VAC, 50~60Hz                  |        |       |
|                          | DC (Optional)        | +5V                                  |        |       |
| Accessory                | Collimator           | Optional                             |        |       |
|                          | Laser Safety Goggles | Optional                             |        |       |

