


■ Features

1. Peak wavelength at 25°C : 655 nm (typical)
2. Standard light output : 5mW (Pulse)
3. Low divergence angle

■ Applications

1. DVD player/ROM/Combo drive
2. Bar code scanner
3. Medical equipment
4. Measurement equipment
5. Printing industry

■ External dimensions(Unit : μm)



P-electrode and N-electrode are both gold pads.



UNION OPTRONICS CORP.

No.156, Gaoshih Rd., Yangmei Township, Taoyuan County 326, Taiwan (R.O.C.)

TEL: 886-3-485-2687 FAX : 886-3-475-4378

E-mail: sales@uocnet.com

Website: <http://www.uocnet.com>

■ Absolute Maximum Ratings(Tc=25°C)

Parameter	Symbol	Ratings	Units
Optical Output	Po	7	mW
Reverse Voltage	Vr	2	V
Storage Temperature	Tstg	-15~+85	°C

■ Electrical and Optical Characteristics(Tc=25 °C)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit	
Threshold Current	Ith	Po=5mW	-	23	27	mA	
Operating Current	Iop	Po=5mW	-	31	35	mA	
Operating Voltage	Vop	Po=5mW	-	2.2	2.3	Volts	
Slope Efficiency	η	3.75mW-1.25mW	0.45	0.63	-	mW/mA	
		I _{3.75mW} -I _{1.25mW}					
Monitor Current	Im	Po=5mW	-	0.2	0.5	mA	
Beam Divergence (FWHM)	Parallel	$\theta //$	Po=5mW	5	8	12	deg.
	Perpendicular	$\theta \perp$	Po=5mW	24	28	32	deg.
Lasing Wavelength*	λ	Po=5mW	645	655	665	nm	

◎ $\theta //$ and $\theta \perp$ are defined as the angle within which the intensity is 50% of the peak value.

◎ Measuring Conditions : Pulse width=5 μ s , Duty cycle=1%

■ Precautions

QUALITY ASSURANCE

After any processing of laser chip or laser diode TO-CAN (LD) by the customer, the performance, yield and reliability of the product, in which the chip or LD is applied, are subject to change due to customer's handling, assembly, testing, and processing. Because laser chip and LD are strongly affected by environmental conditions, physical stress, and chemical stresses imposed by customer that are not in Union Optronics Corp. (UOC) control and hence no guarantee on the characteristics and the reliability at all after the shipment. Also, UOC does not have any responsibility for field failures in a customer product. When attaching a heat sink to laser chip or LD, be careful not to apply excessive force to the device in the process.

SAFETY PRECAUTIONS

Although Union Optronics Corp. (UOC) keeps improving quality and reliability of its laser chip and laser diode TO-CAN (LD), semiconductor devices in general can malfunction or fail due to their intrinsic characteristics. Hence, it is required that the customer's products are designed with full regard to safety by incorporating the redundancy, fire prevention, error prevention so that any problems or error with UOC laser chip or LD does not cause any accidents resulting in injury, death, fire, property damage, economic damage,



or environmental damage. In case customer wants to use UOC laser chip or LD in the systems requiring high safety, customer is requested to confirm safety of entire systems with customer's own testing.

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The information provided by Union Optronics Corp. (UOC), including but not limited to technical specifications, recommendations, and application notes relating to laser chip or laser diode TO-CAN (LD) is believed to be reliable and accurate and is subject to change without notice. UOC reserves the right to change its assembly, test, design, form, specification, control, or function without notice.

